



SINGLESAND/WATER BOWL

902-806-S

Important

Please retain this instructions sheet in your files. It contains important replacement parts information. All equipment should be installed in accordance with these instructions.

It is important to use and maintain all public playground equipment properly. Playground equipment which is improperly maintained can cause serious injury. Periodical inspections and maintenance, repair and/or replacement of damaged parts is necessary for safe operation of equipment and safety of users. Resilient surfacing should be used under all playground equipment. Appropriate publications, available at no charge, from the Consumer Product Safety Commission, include "A Handbook For Public Playground Safety". You can receive your free copy by calling 1-301-504-7908.

General Use/Fall Zone & Footing Recommendations

Stationary & Portable Equipment- Use/Fall zones should extend a minimum of 6 ft. in all directions from the perimeter of the equipment ground space. This area should be covered with the required amount of resilient safety surfacing material. For some equipment use/fall zones can overlap. See Consumer Product Safety Commission Guidelines. Vary soil & climate conditions may require deeper & heavier footing in some areas. Check local building codes for more information

General Assembly Instructions

Check all the parts and hardware with the packing list to be sure you have received everything needed to assemble this product. Contact your distributor with notification of any missing or damaged parts. CONTACT MUST BE MADE WITHIN 10 DAYS OF RECEIPT OF YOUR ORDER.

Only hand-tighten nuts and bolts on initial assembly. Final tightening should be done evenly after final assembly is complete. ANY ENDS OF BOLTS PROTRUDING BEYOND NUTS SHOULD BE CUT OFF AND/OR PEENED OVER TO REMOVE ANY SHARP EDGES. Go over the entire unit to file smooth any sharp edges or projections that may have been caused by rough handling in shipping or installation

General Maintenance Instructions

Check Monthly for loose bolts, damaged or broken parts. Tighten and/or replace immediately.

INSTALLATION INSTRUCTIONS

NOTE: READ AND REVIEW INSTRUCTIONS BEFORE BEGINNING INSTALLATION.

1. Install legs to the 4 holes in the flower panel and tighten as shown in detail B.
2. Place the Bubble Dome into the cut out in the flower panel and line up the holes, and install hardware as shown in Detail A. DO NOT OVER TIGHTEN, THE BUBBLE COULD BREAK.
3. Finally install drains into bubble (this is an option). You must locate the lowest point of the bubble and drill a 1-1/8" hole at the lowest point. CAUTION DRILL SLOWLY. Install the drain assembly as shown in Detail C. NOTE: A small bead of silicone may be placed under the rubber gasket if a leak is detected.

