



SportsPlay Equipment, Inc.

5642 Natural Bridge St. Louis, MO 63120

SportsPlay Baseball Backstop Specifications

The backstop shall be constructed with SportsPlay Sportpanels. The Sportpanels shall be a welded 5' x 10' frame with one center brace and wired with chain link fencing.

The tubing to fabricate the frame shall be 1.029 OD x 14 gauge galvanized steel tube. The bending strength of the tubing shall equal or exceed that of Schedule 40 pipe. The weight of the hot dipped zinc coating shall be 1.0 oz. /sq. ft. A chromate conversion coating shall be applied to the zinc. A clear thermoplastic electrostatically applied acrylic coating shall be .5mil \pm 0.1 thick.

The wire fence shall be attached to the frame using ½" wide x .020" stainless steel banding and 3/8" aluminum tension rods. The chain link fence shall be 2" by 11 gauge knuckle-knuckle. After weaving, the fence shall be hot dipped galvanized to a zinc coating of 2 oz/sq. ft.

Posts and hood supports shall be 2.275 OD x 13 gauge galvanized steel tube. The bending strength of the tube shall equal or exceed that of Schedule 40 pipe. The weight of the hot dipped zinc coating shall be 1.0 oz/sq. ft. \pm .1oz/sq. ft. A chromatic conversion coating shall be applied to the zinc. A clear thermoplastic electrostatically applied acrylic coating shall be .5 mil \pm 0.1 mil thick.

All clamps shall be pressed steel hot dipped galvanized. All hardware shall be zinc coated.

AAA State of Play offers [Baseball Equipment](#) including a [Baseball Backstop](#).

AAA State of Play
10725 Hidden Oak Way
Indianapolis, IN 46236
www.aaastateofplay.com



Local (317) 826-2777
Toll Free (877) 826-2776
Fax (317) 823-3567